



Chemieresin Industries Pvt. Ltd.

Plot No. 901/A, Phase - 4, GIDC - Naroda, Ahmedabad - 382330

Technical Data Sheet

Product : CR 120 Clear

Description :

CR 120 Clear is a low viscous reactive diluent modified epoxy resin based on bisphenol - A. Due to low viscosity it is capable of high filler loading and excellent wetting property. It can be cured with various hardeners like polyamidoamide, phenalkamines, aliphatic amines, cycloaliphatic amines, and adducts. The appropriately cured material is able to provide good combination physical and mechanical properties.

Advantages :

High filler loading
Low viscosity and light colour

Applications :

Crack filling and repair
Primer and grouts
Screed, mortar and mastics
Solvent free coating and floorings
River Table Top

Processing :

Spray, roller or brush

Typical specifications :

Properties	Unit	Values
-------------------	-------------	---------------

Appearance	-	Clear Liquid
Colour	GS	Max 1
Epoxy value	Eq/kg	5.0 - 5.3
Viscosity at 25°C	mPas	1000 - 1500
Epoxy equivalent weight (EEW)	g/eq	190 - 200

Packaging :

CR 120 Clear is available in 200 kg HDPE drums. Other packing may be considered on request.

Storage and Handling :

CR 120 Clear should be stored in a cool and dry place, preferably in a sealed container and should not be exposed to direct sunlight. This product has a shelf life of 2 years, if stored in its original container between 18°C and 25°C away from humidity and excessive heat. Please refer to the Safety Data Sheet (SDS) for detailed instructions on storage and handling.

Safety :

Wear personal protective equipment (PPE). Avoid contact with the eyes and skin. In case of direct contact and irritation, the resin should be washed off immediately with soap and warm water. Avoid breathing vapours, mist or gas. Please refer to the SDS for detailed safety instructions.

Spills and Disposal :

In case of spills, sweep up and shovel the spilled material. Keep spilled material in suitable, closed containers for disposal. Soak up with an absorbent such as clay, sand or other suitable material. Flush area with water to remove trace residue. Do not allow the product to reach the sewage system. Waste must be disposed of in accordance with federal, state or local regulations, as applicable.